

# PARMA

## SPECIFICATION

Quality		: <b>PARMA</b>
Product definition		: tufted cut pile, frisee
Gauge		: 1/10"
No. of tufts	ISO 1763	: ± 178000/m <sup>2</sup>
Pile fibre		: 100% polyamide nylon ECONYL
Pile weight	ISO 8543	: 1100 gr/m <sup>2</sup> ± 5%
Pile height	ISO 1766	: 5.5 mm ± 5%
Primary backing		: PA/PES non-woven - Colback
Tile backing		: Polyflex
Total thickness	ISO 1765	: 8.5 mm ± 5%
Total weight	ISO 8543	: 4800 gr/m <sup>2</sup> ± 7,5%
Tile size		: 50 x 50 cm (± 19.7" x 19.7")
Tiles per box		: 20

## PERFORMANCE

Use classification	EN 1307	: Class 33
Castor chair test	EN 985	: A. continuous use
Abrasion	ISO 12951	: pass
Vettermann test	ISO TR 10361/EN 1471	: pass
Thermal isolation	ISO 8302	: 0.07 m <sup>2</sup> K/W
Dimensional stability	EN 986 - EN 1307	: pass
Luxury/Comfort	EN 1307	: classe 5
Sound Absorption	ISO 140-8	: 24dB

## ELECTROSTATIC PROPERTIES

Walk on test	ISO 6356	: -2.0 kV
Horizontal electrical resistance	ISO 10965	: 7.9x10 <sup>12</sup> Ω
Vertical electrical resistance	ISO 10965	: 4.8x10 <sup>11</sup> Ω
Static loading		: anti-static

## FLAME PROPERTIES

Reaction to fire	EN ISO 11925-2	
	EN ISO 9239-1	: Bfl - s1
Hot metal nut test	BS 4790	: Low Radius

## COLOUR FASTNESS PROPERTIES

Light	ISO 105 B02	: 4-5
Rubbing, dry	ISO 105 X12	: 5.0
Rubbing, wet	ISO 105 X12	: 5.0
Water	ISO 105 E01	: 4-5
Water stains	EN 1307/EN 15115	: 5.0

## GENERAL

Recommended maintenance:  
Pile direction:

Laying instructions:

Best results are obtained when cleaned with a dry shampoo method.  
Directional arrows are printed on the back of each tile.  
Best results are obtained when laid checkerboard.

Tiles require no underlay, nailing, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 30 m<sup>2</sup> it is advisable to use double sided adhesive tape on every 8th row or a tackifier.

**CE**  
EN14041



**ECONYL**



Specification in accordance EN 1307