

Date of receipt: 14/12/21

Date of issue: 27/01/22

Report consists of 9 test reports.

Defects before testing: None

Sample name: MUZIO K240/T1

BRADO S.P.A. VIA CAL DI MEZZO 3 31030 BIGOLINO DI VALDOBBIADENE (TV) ITALIA

SAMPLE N° 321550

Overall dimensions: 750 x 750 x 1050 (h) mm

List of test reports:

- 1. Office work chair Dimensions EN 1335-1:2020
- 2. General design requirements EN 1335-2:2018, clauses 4.1 4.2
- 3. Information for use EN 1335-2:2018, clause 6
- 4. Work chairs: seat and back static load test EN 1728:2012+AC:2013
- 5. Work chairs: seat and back durability EN 1728:2012+AC:2013
- 6. Work chairs: arm rests durability EN 1728:2012+AC:2013
- 7. Work chairs: arm rest downward static load test-central EN
- 1728:2012+AC:2013
- 8. Stability EN 1022:2018, clause 7.3
- 9. Work chairs: rolling resistance of unloaded chair EN 1728:2012+AC:2013



This document is part of a PDF file digitally signed by Franco Bulian.

The manading director Dr. Franco Buliar e



SAMPLE N° 321550

| Date of issue: |
|----------------|
| Sample weight: |
| Sample name: |

27/01/22 Not determined MUZIO K240/T1



Side view



Rear view



Bottom view



Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



TEST REPORT 321550 / 1

| | • | SUM |
|------------------|-----------|------|
| Revision: | 0 | |
| Date of receipt: | 14/12/21 | |
| Date of test: | 20/12/21 | |
| Date of issue: | 27/01/22 | |
| Sample name: | MUZIO K24 | 0/T1 |



BRADO S.P.A. VIA CAL DI MEZZO 3 31030 BIGOLINO DI VALDOBBIADENE (TV) ITALIA

Office work chair - Dimensions EN 1335-1:2020

| Method: ISO 24496:2017 | | | | |
|-------------------------|-------|--|--|--|
| | | | | |
| 1. General features | | | | |
| 1.1 Seat | | | | |
| depht: | х | fixed | | |
| | - | adjustable with horizontal movement | | |
| inclination: | - | fixed | | |
| | х | adjustable | | |
| 1.2 Backrest | | | | |
| height: | Х | fixed | | |
| | - | adjustable | | |
| | Х | adjustable lumbar support (height) | | |
| | - | adjustable lumbar support (protrusion) | | |
| inclination: | - | fixed | | |
| | х | adjustable | | |
| 1.3 Seat and back syncr | onyze | d yes | | |
| 1.4 Armrests | | | | |
| height: | - | fixed | | |
| | х | adjustable | | |
| depth: | - | fixed | | |
| | x | adjustable | | |
| clear distance: | x | fixed | | |
| | - | adjustable | | |
| rotation: | no | | | |
| | | | | |

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian nei OLC 0



TEST REPORT Date of issue: Sample name: **321550 / 1 rev. 0** 27/01/22 MUZIO K240/T1

www.catas.com

CATAS S.p.A. via Antica, 24/3

33048 San Giovanni al Nat. (UD)

+39 0432 747211 - lab@catas.com

Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



| fest Res | ults | | | |
|-----------|---|---------------------------------------|-----------------|-------|
| | limensions are in mm | | | |
| ype of o | chair: B | I I I I I I I I I I I I I I I I I I I | | |
| symbol | parameter | requirement | measured | con |
| | SEAT | ГТ | | |
| а | seat height and sitting height | 420 to 510 | 408 to 521 | yes |
| | adjustment range | 100 min | 113 | ye |
| b | seat depth adjustable | 425 to 445 | 1 | / |
| | adjustment range | 50 min | 1 | / |
| | seat depth not adjustable | within 425 and 485 | 448* | ye |
| С | seat pad depth | 380 min | 422 | ye ye |
| d | seat pad width | 400 min | 442 | ye |
| е | seat pad angle - adjustable | -2° | -12° to -1°* | ye ye |
| | adjustment range | 5° | 11° | ye |
| | seat pad angle - not adjustable | + 2° ÷ - 5° | / | / |
| | BACK REST minimum and maximum lumbar support | [] | 150 to 320 | |
| | | 50 min | 130 of 170 | |
| f | difference (fmax - fmin) within 170 mm and 300 mm | 50 min | 130 01 170 | ye |
| | range of the backrest / lumbar support | 50 min | 1 | / |
| | height of lumbar support - not adjustable | within 170 and 300 | 1 | / |
| h | backrest height | 360 min | 530 | ye ye |
| j | backrest width | 360 min | 449 | ye ye |
| k | horizontal radius of the back rest | 400 min | > 400 | ye ye |
| Ι | back rest inclination (adjustment range) | 15° min | 37° | ye |
| у | angle between seat and back | 90° min | 116° | ye |
| | ARM REST | | | |
| n | length of arm rest | 150 min | 228 | ye ye |
| 0 | width of arm rest | 40 min | 74 | ye |
| р | height of armrest - adjustable | 225 to 250 | 180 to 252* | ye |
| | adjustment range | 50 min | 72 | ye |
| | height of armrest - not adjustable | within 225 and 275 | 1 | / |
| q | distance from the bachrest to the front of the armrests | 350 max | 318* | ye |
| r | hip breadth clearance with armrests in widest position | 460 min | 538 | ye |
| z | Clear distance between the armrests pads - adjustable | 460 to 510 | 1 | / |
| | Clear distance between the armrests pads - not adjust. | within 460 and 510 | 490* | ye |
| | UNDERFRAME | · · · · · | | |
| S | maximum offset of the underframe | 415 max | 391 | ye |
| | foot support | Ø > 20 mm or flat | | / |
| The limit | is included in the uncertainty interval associated with the mea | sured value (see table | 1 on page 3/3). | |

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian 0.0 u e 0



TEST REPORT Date of issue: Sample name: **321550 / 1 rev. 0** 27/01/22 MUZIO K240/T1

CATAS S.p.A. via Antica, 24/3

www.catas.com

33048 San Giovanni al Nat. (UD)

+39 0432 747211 - lab@catas.com

Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



| symbol | Parameter | Uncertain at 95% confidence level (k=2) |
|--------|---|--|
| | SEAT | |
| а | seat height and sitting height | ± 8 mm (seat) ± 15 mm (sitting) |
| b | seat depth | ± 25 mm |
| с | seat pad depth | ± 25 mm |
| d | seat pad width | ± 10 mm |
| е | seat angle | ± 2° |
| | BACK REST | |
| f | height of lumbar support | ± 25 mm |
| h | backrest height | ± 15 mm |
| j | backrest width | ± 10 mm |
| k | horizontal radius of the back rest | Not applicable |
| I | back rest inclination | ± 4° |
| у | angle between seat and back | ± 4° |
| | ARM REST | |
| n | length of arm rest | ± 5 mm |
| 0 | width of arm rest | ± 5 mm |
| р | height of armrest | ± 10 mm |
| q | distance from the bachrest to the front of the armrests | ± 40 mm |
| r | hip breadth clearance with armrests in widest position | ± 20 mm |
| z | Clear distance between the armrests pads | ± 60 mm |
| | UNDERFRAME | |
| S | maximum offset of the underframe | ± 8 mm |

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian 0.0 n e 0



Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



TEST REPORT 321550 / 2

| Revision: | 0 |
|------------------|----------|
| Date of receipt: | 14/12/21 |
| Date of test: | 26/01/22 |
| Date of issue: | 27/01/22 |
| | |

Sample name:



BRADO S.P.A. VIA CAL DI MEZZO 3 31030 BIGOLINO DI VALDOBBIADENE (TV) ITALIA

General design requirements EN 1335-2:2018, clauses 4.1 - 4.2

| Requirements | Remarks |
|--|-------------------------------|
| Clause 4.1 | |
| a) Edges of seat, back rest and arm rests in contact by the user are rounded ≥ 2 mm | Yes |
| b) Edges of handles are rounded or chamfered in the direction of the force applied | Yes |
| c) All other edges and corner are free from burrs and rounded or chamfered | Yes |
| d) Ends of accessible hollow components are closed or capped | Hollow components not present |
| It shall not be possible for any load bearing part to come loose unintentionally | Yes |
| Clause 4.2 | |
| Absence of shear and squeeze points, created by parts operated by powered mechanism. | Yes |
| Absence of shear and squeeze points, created by loads applied during normal use. | Yes |

The test results comply with the requirements in clauses 4.1 and 4.2 of EN 1335-2:2018

Note: evaluation of accessible parts has been carried out according to CEN TR 17202:2018, clause 6.

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian e-OLC



Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



TEST REPORT 321550 / 3

| | | The start of the s |
|------------------|-----------|--|
| Revision: | 0 | |
| Date of receipt: | 14/12/21 | |
| Date of test: | 27/01/22 | |
| Date of issue: | 27/01/22 | |
| Sample name: | MUZIO K24 | 0/T1 |



BRADO S.P.A. VIA CAL DI MEZZO 3 31030 BIGOLINO DI VALDOBBIADENE (TV) ITALIA

Information for use EN 1335-2:2018, clause 6

| Statement checked | Remarks |
|---|------------------|
| Information for use in the language of the country in which the chair will be delivered to the end user. | Italian language |
| a) Information regarding the intended use. | Present |
| b) Information regarding possible adjustments | Present |
| c) Instruction for operating the adjusting mechanisms. | Present |
| d) Instruction for the care and the maintenance of the chair. | Present |
| e) Information for chairs with seat height adjustements with energy accumulators that only trained personnel may replace or repair seat height adjustement components with energy accumulators. | Present |
| f) Information on the choice of castors in relation to the floor surface. | Present |

The test results comply with the requirements in clause 6 of EN 1335-2:2018

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian nei OLC 0



Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



TEST REPORT 321550 / 4

| Revision: | 0 |
|------------------|-------|
| Date of receipt: | 14/12 |
| Date of test: | 22/1 |
| Date of issue: | 27/0 |
| | |

Sample name:



BRADO S.P.A. VIA CAL DI MEZZO 3 31030 BIGOLINO DI VALDOBBIADENE (TV) ITALIA

Work chairs: seat and back static load test EN 1728:2012+AC:2013

Test performed according to EN 1335-2:2018 Seat and back static load test, clause 7.3 of EN 1728:2012+AC:2013 Seat height: highest position

Seat inclination:horizontalBack rest in height:/Seat in depth:/Position of castorsperpendicular to the base armsTension of mechanism spring:medium



Test results:

| Seat load N | Back force N | Number of cycles | Loading point | Back rest inclination mechanism | Remarks |
|----------------|-----------------|---------------------|------------------|---------------------------------------|------------|
| 1.600 | 560 | 5 | A - B | Blocked | No defects |
| 1.600 | 560 | 5 | A - B | Unlocked | No defects |

Seat front edge static load, clause 7.4 of EN 1728:2012+AC:2013

Seat height: highest position

Seat depth: /

Test results:

| Seat load N | Number of cycles | Loading point | Remarks |
|----------------|---------------------|------------------|------------|
| 1.600 | 10 | F | No defects |

The test results comply with the requirements in clause 5.2 of EN 1335-2:2018

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian 0-



Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



TEST REPORT 321550 / 5

| Revision: | 0 |
|------------------|------|
| Date of receipt: | 14/1 |
| Date of test: | 22/1 |
| Date of issue: | 27/0 |
| | |

Sample name:



BRADO S.P.A. VIA CAL DI MEZZO 3 31030 BIGOLINO DI VALDOBBIADENE (TV) ITALIA

Work chairs: seat and back durability EN 1728:2012+AC:2013

Test performed according to EN 1335-2:2018 Seat and back durability clause 7.9 of EN 1728:2012+AC:2013 H R Seat height: highest position Seat inclination: horizontal D Back rest in height: 1 Seat in depth: 1 Position of castors: perpendicular to the base arms Tension of mechanism spring: medium Test results:

| Number of cycles | | Force N | Back rest inclination mechanism | Remarks |
|---------------------|----|--------------|---------------------------------------|------------|
| 120.000 | A | 1.500 | Unlocked | No defects |
| 40.000 | СВ | 1200 320 | Locked | No defects |
| 40.000 | СВ | 1200 320 | Unlocked | No defects |
| 20.000 | JE | 1200 320 | Unlocked | No defects |
| 20.000 | FH | 1200 320 | Unlocked | No defects |
| 20.000 | DG | 1100 1100 | Unlocked | No defects |

The test results comply with the requirements in clause 5.2 of EN 1335-2:2018

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian e:



Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



TEST REPORT 321550 / 6

| Revision: | 0 |
|------------------|----------|
| Date of receipt: | 14/12/21 |
| Date of test: | 21/01/22 |
| Date of issue: | 27/01/22 |
| | |

Sample name:



BRADO S.P.A. VIA CAL DI MEZZO 3 31030 BIGOLINO DI VALDOBBIADENE (TV) ITALIA

Work chairs: arm rests durability EN 1728:2012+AC:2013

Test performed according to EN 1335-2:2018

Arm rest durability, clause 7.10 of EN 1728:2012+AC:2013

Seat height:lowest positionSeat inclination:horizontalArmrest positioning:highest and outermost

Test results:

| Load on arm rest N | Number of cycles | Remarks |
|--------------------------|---------------------|------------|
| 400 | 60.000 | No defects |

The test results comply with the requirements in clause 5.2 of EN 1335-2:2018

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian e:



Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



 TEST REPORT

 321550 / 7

 Revision:
 0

 Date of receipt:
 14/1

| Date of receipt: | 14/12/21 |
|------------------|----------|
| Date of test: | 26/01/22 |
| Date of issue: | 27/01/22 |
| Sample name: | MUZIO K |



BRADO S.P.A. VIA CAL DI MEZZO 3 31030 BIGOLINO DI VALDOBBIADENE (TV) ITALIA

Work chairs: arm rest downward static load test-central EN 1728:2012+AC:2013

Test performed according to EN 1335-2:2018

Arm rest downward static load test - central, clause 7.5 of EN 1728:2012+AC:2013

| Seat height: | lowest position |
|----------------------|-----------------------|
| Seat inclination: | horizontal |
| Armrest positioning: | highest and outermost |

Test results:

| Load on the arm rest N | Number of cycles | Remarks |
|---------------------------|---------------------|------------|
| 750 | 5 | See note |
| 900 | 5 | No defects |

Note: after the functional load of 750 N the chair does not overbalance.

The test results comply with the requirements in clause 5.2 of EN 1335-2:2018

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian e: OLC



Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



TEST REPORT 321550 / 8

| | - | SVI~ |
|------------------|-----------|------|
| Revision: | 0 | |
| Date of receipt: | 14/12/21 | |
| Date of test: | 26/01/22 | |
| Date of issue: | 27/01/22 | |
| Sample name: | MUZIO K24 | 0/T1 |



BRADO S.P.A. VIA CAL DI MEZZO 3 31030 BIGOLINO DI VALDOBBIADENE (TV) ITALIA

Stability EN 1022:2018, clause 7.3

| Type of chair: tilting | | |
|--|---|-------------------|
| Positioning of chair components: as specified in Table 1 of EN 1022:2018 | | |
| Loads and masses according to table B1 of EN 1022:2018, annex E | 3 | |
| Forwards overturning | | |
| Forwards overturning, clause 7.3.1 | : | does not overturn |
| Forwards overturning for seating with foot rest, clause 7.3.2 | : | 1 |
| Corner stability, clause 7.3.3 | : | does not overturn |
| Sideways overturning | | |
| Sideways overturning, all seating without arm rests, clause 7.3.4 | : | 1 |
| Seating with arm rests, clause 7.3.5.2 | : | does not overturn |
| Seating with raised side edges, clause 7.3.5.3 | : | 1 |
| Rearwards overturning | | |
| Rearwards overturning all seating with back rests, clause 7.3.6 | | |
| Minimum force required: 134 N | : | does not overturn |
| Tilting seating, clause 7.4.2 | : | does not overturn |
| Reclining seating with leg rest, clause 7.4.3 | : | |
| Reclining seating without leg rest, clause 7.4.4 | : | |
| Rearwards stability test for rocking chairs, clause 7.4.5 | : | |
| Note: The test has been carried out after the functional load on the arm rest. | | |
| The test results comply with the requirements in clause 4.4 of EN 1335-2:2018. | | |
| | | |

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian nei OLC 0



Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



TEST REPORT 321550 / 9

| Revision: | 0 | |
|------------------|-----------|------|
| Date of receipt: | 14/12/21 | |
| Date of test: | 26/01/22 | |
| Date of issue: | 27/01/22 | |
| Sample name: | MUZIO K24 | 0/T1 |

Con-

BRADO S.P.A. VIA CAL DI MEZZO 3 31030 BIGOLINO DI VALDOBBIADENE (TV) ITALIA

Work chairs: rolling resistance of unloaded chair EN 1728:2012+AC:2013

Test performed according to EN 1335-2:2018

Rolling resistance of unloaded chair, clauses 6.30 and 7.14 of EN 1728:2012+AC:2013

| Type of castors: | W |
|------------------|-----------------|
| Test surface: | steel floor |
| Test speed: | 50 mm/s |
| Seat height: | lowest position |

Test results:

| Measured resistance of castors N | Minimum allowed resistance N | Remarks |
|--|---------------------------------|------------|
| 34 | 12 | No defects |

Unless otherwise specified, measurement uncertaintie expanded to a confidence level of about 95% are ±2,0 N.

The measurement uncertainties stated in this document have been determined according to UNI CEI ENV 13005:2000. They were estimated as expanded uncertainty obtained multiplying the standard uncertainty by the coverage factor k corresponding to a confidence level of about 95%. Normally k=2.

The test results comply with the requirements in clause 5.2 of EN 1335-2:2018

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian e: