REPORT N. 053-2021-CR Eng

UNI EN ISO 354:2003
ACOUSTIC ABSORPTION MEASUREMENT IN REVERBERATION ROOM

Issue place and date: Cerea (VR), 21/11/2022

Committee: CENTRUFFICIO LORETO SPA – CUF MILANO

Address committee:: Viale Andrea Doria, 17 – 20124 Milano

Sample delivery date: 3rd November 2021

Sample provenance: CENTRUFFICIO LORETO SPA – CUF MILANO

Sample installation date: 4th November 2021

Sample installed in laboratory by: Committee (sampling made by the committee)

Test date: 4th November 2021

Test location: Z Lab S.r.l. – Via Pisa, 7 – 37053 Cerea (VR) - Italia

Sample denomination: SHAPES - thickness 30 mm

Mounting Type: Mounting E480

LAB N° 1416 L

PREPARED	VERIFIED	APPROVED
Sabato Di Filippo	Antonio Scofano	Antonio Scofano

LAB N° 1416 L

Acoustic absorption calculation in reverberation room according to UNI EN ISO 354:2003

Sample description: SHAPES - thickness 30 mm
Mounting Type: Mounting E480

Sample area: 10,80 m²
Reverberation room volume: 161,3 m³

| f [Hz]	α_S [-]
Frequency	*Acoustic absorption coefficient values*
100	0,68
125	0,52
160	0,62
200	0,64
250	0,66
315	0,66
400	0,57
500	0,71
630	0,78
800	0,79
1000	0,82
1250	0,78
1600	0,82
2000	0,82
2500	0,78
3150	0,70
4000	0,69
5000	0,68

Evaluation based on laboratory measurement results by means of a technical method.

M-TEC-39 eng rev.9
29-12-2020

This test report consists of n. 11 pages and cannot be reproduced, but in full, without the written permission of Z Lab Srl. The results reported in this document refer only to the sample and the materials to be tested as well as received. The laboratory decline all responsibility for the data provided by the customer. The samples are kept for 30 days after the end of the test.

Page 10 of 11

LAB N° 1416 L

Acoustic absorption calculation in reverberation room according to UNI EN ISO 11654:1998

Sample description: SHAPES - thickness 30 mm
Mounting Type: Mounting E480

Sample area: 10,80m²
Reverberation room volume: 161,3 m³

f [Hz]	α_p [-]
Frequency	*Practical acoustic absorption coefficient values*
125	0,60
250	0,65
500	0,70
1000	0,80
2000	0,80
4000	0,70

STANDARD EVALUATION INDEX:

α_w	0,8 CLASS B	*Weighted acoustic sound absorption coefficient* *Sound Absorption Class ****	*UNI EN ISO 11654:1998*

Evaluation based on laboratory measurement results by means of a technical method.

** Classification of acoustic absorbers: The unique αw evaluation index is used to calculate the absorption class according to the following table:

CLASS	α_w
A	0.9 - 0.95 - 1.00
B	0.8 - 0.85
C	0.6 - 0.65 - 0.7 - 0.75
D	da 0.3 a 0.55
E	0.15 - 0.2 - 0.25
NC	0.00 - 0.05 - 0.1

Laboratory Manager, Ing. Antonio Scofano