


# ARTESIA SS




0,48 m<sup>3</sup> - 29,5 kg  
60x56x51 cm

54x60x92cm  
4 pcs [carton]

Stackable on floor [20pcs]  
Impilabile a terra [20pz]

Chromed or epoxy powder painted wire steel  $\varnothing$ 11mm sled frame with armrests, techno-polymer shell.  
Struttura a slitta in filo metallico  $\varnothing$ 11mm con braccioli, cromata o verniciata, scocca in tecnopolimero.




## FIRE RETARDANT

IGN Versions follows UNI 9177 certification in terms of Fire Resistance, Fire Reaction Class 1.  
Versioni IGN prodotto Omologato con Classe di Reazione al fuoco 1, UNI 9177.



## FRAME FINISHES



Black glides on black frames. Neutral glides on other frame finishes.  
Piedini neri su telai neri. Piedini neutri nelle altre finiture telai.

## ACCESSORIES

### NARROW CUSHION | CUSCINO STRETTO

Narrow upholstered cushion, suitable for chairs stackability (width 390mm).

Cuscino tappezzato stretto, adatto a sedute che devono essere impilate (larghezza 390mm).



### WIDE CUSHION | CUSCINO LARGO

Large upholstered cushion (width 440mm).

Cuscino tappezzato largo (larghezza 440mm).



### CUSHION AVAILABLE FABRICS

[B] Blazer Fabric

[DK] Kvadrat Fabric - Steelcut 2

[DK] Kvadrat Fabric - Remix 2

[E] Synthetic Leather Aurea

[K] King Fabric

[TC] COM Fabric

Narrow cushion fabric required 4pcs: Lin Mtrs 1 (h 1,40)

Large cushion fabric required 4pcs: Lin Mtrs 1,2 (h 1,40)

White flexible polyurethane foam, density 30kg/m<sup>3</sup>, flame retardant according to the method:  
UNI 9175 - UNI 9175 / FA1, Class 1IM.

Poliuretano espanso flessibile di colore bianco, densità 30kg/m<sup>3</sup>, ignifugo secondo il metodo:  
UNI 9175 - UNI 9175/FA1, Classe 1IM.