

LISBOA



Specifications and tolerances in according EN 1307

COSTRUZIONE	CONSTRUCTION	TECHNIQUE DE FABRICATION	HERSTELLUNGSVERFAHREN
TUFTING RICCIO 1/10"	TUFTED LOOP PILE 1/10"	TUFTED BOUCLÉ 1/10"	GETUFTED SCHLINGE 1/10"
COMPOSIZIONE	COMPOSITION	COMPOSITION	POLNUTZSCHICHT
100% POLIAMMIDE SD	100% POLYAMIDE SD	100% POLYAMIDE SD	100% POLYAMID SD
SOTTOFONDO	SECONDARY BACKING	DOSSIER	RÜCKENAUSRÜSTUNG
POLYFLEX	POLYFLEX	POLYFLEX	POLYFLEX
PUNTI AL M²	STITCHES PER M²	TOUFFES AU M²	KNOTEN M²
± 189600	± 189600	± 189600	± 189600
ALTEZZA PELO	PILE HEIGHT	HAUTEUR DU VELOURS	POLHÖHE
± 3.0 mm	± 3.0 mm	± 3.0 mm	± 3.0 mm
ALTEZZA TOTALE	TOTAL HEIGHT	HAUTEUR TOTALE	GESAMTHÖHE
± 5.6 mm	± 5.6 mm	± 5.6 mm	± 5.6 mm
PESO FIBRA	YARN WEIGHT	POIDS DU VELOURS	POLGEWICHT
± 740 g/m²	± 740 g/m²	± 740 g/m²	± 740 g/m²
PESO TOTALE	TOTAL WEIGHT	POIDS TOTAL	GESAMTGEWICHT
± 4200 g/m²	± 4200 g/m²	± 4200 g/m²	± 4200 g/m²
DIMENSIONI QUADROTTA	TILE SIZE	TAILLES DES DALLE	GESAMTGEWICHT
50x50 cm	50x50 cm	50x50 cm	50x50 cm
FAMIGLIA TUFTING 26	FAMIGLIA TUFTING 26	FAMIGLIA TUFTING 26	FAMIGLIA TUFTING 26



BUSINESS WEARABILITY: ★ ★ ★

Colour fastness to light	> 5	Thermal resistance m² K/W	≤ 0,17
Insulation impact noise ΔLw	24 dB	Body voltage walking test kV	≤ 2

TSO1/2024