Twilight
Design: Patricia Urquiola

Type: Dim-out curtain
Composition: 59% polyester FR, 41% polyester
Yarn type: Filament
Binding: Satin
Width: Approx. 300 cm, 118 inches
Weight: Approx. 1080 g/lin.m, 34.8 oz/ly

Colour difference may occur

Cleaning: Washing at max. 60°C. Drip drying.
Shrinkage approx. 1% when washed at 60°C.
Ironing might be necessary
More info: Care and maintenance kvadrat.dk

Disinfection, see www.kvadrat.dk

10 year warranty

0575/21

Acoustic

Twilight

Lightfastness
Note 5-6 ISO 105-B02

Light Reflection DIN EN 410
8-48% (test is performed in flat state)

Light Transmission DIN EN 410
0-0.8% (test is performed in flat state)

Absorption
0.55/Class D (flat), 0.80/Class B (waved) EN ISO 354

Airflow
1374 Pa s/m EN 29053

Flame resistance
AS/NZS 1530.3
ASTM E84 Class A Adhered
ASTM E84 Class A Unadhered
BS 5867 part 2 type B
DIN 4102 B1
EN 13501 B-s1, d0
EN 13 773 class 1
IMO FTP Code 2010 Part 7
NF P 92 507 M1
NFPA 701
SN 198 898 5.2
UNI 9177 Classe 1

Quality benefits
+ 99% dim-out
Good lightfastness
Permanent flame retardant
Washable
Acoustic performance

Environmental benefits
Follow the EU Ecolabel dye restrictions incl. AZO dye and REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant
Healthier Hospitals compliant

Green Building certificates
Greenguard Gold: Low chemical emission
Environmental Product Declaration (EPD): Based on a LCA following EN 15804 and follow the standards of ISO 14040
Health Product Declaration (HPD): Declaring textile content and substance

Country of origin
Turkey